



CreativeWEAVE

form function solution

Futura 2110x30 Twist



WORLD WIDE WEAVE

Technische Daten Technical Data Sheet / Fiche Technique / Información Técnica

Werkstoff Material / Matériau / Material	Edelstahl 1.4404 (AISI 316L) Stainless Steel / Acier inoxydable / Acero inoxidable	
Freie Fläche Open area / Surface ouverte / Superficie abierta	ca. 82 %	
Drahtstärke Wire diameter / Diamètre des fils / Diametro de hilos	Kettseilgruppe: 2 x 2,75 mm Cable / Cable / Cable	Schussstab: 4 mm Rod / Tringle / Varilla
Teilung Kettseilgruppe Cable pitch / Entraxe cables / Paso cables	110 mm	
Teilung Schuss Weft wire pitch / Entraxe tringles / Pasa trama	30 mm	
Dicke Thickness / Epaisseur / Espesor	ca. 9 mm	
Gewicht Weight / Poids / Peso	ca. 4,1 kg/m ²	
Maximale Gewebebreite Maximum mesh width / Largeur maximale / Ancho máximo	4 m	
Maximale Gewebelänge Maximum mesh length / Longueur de tissu maximale/ Longitud maxima de la tela	25 m	

KO & CO
Architectural Complements

KO & CO BENELUX nv.
Showroom
Boomssesteenweg 41/10
B-2630 Aartselaar
Tel. (+32) (0)3 458 40 40
Fax (+32) (0)3 458 40 00
www.ko-co.com

